

Material Safety Data Sheet

Infosafe No. ACQQL Issue Date: October 2002 ISSUED by CASTROL
Product Name: OBEEN UF3

Not classified as hazardous according to criteria of NOHSC

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product Name

OBEEN UF3

Product Use

Grease for areas of incidental food contact.

Company Name

Castrol Australia Pty. Limited (ABN 87 008 459 407)

Address

132 McCredie Road, Guildford,
NSW, 2161 Australia

Emergency Tel.

1800 638 556

Telephone Number/Fax

Tel: (02) 9795 4800 Fax: (02) 9795 4910

Other Information

Castrol Technical Help Line 1300 557 998 (Local call)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Information on Composition

Polyalphaolefin (PAO) synthetic oil and additives.

| Ingredients | Name | CAS | Proportion |
|-------------|--|--------------|------------|
| | Ingredients determined not to be hazardous | Not required | 100 % |

3. HAZARDS IDENTIFICATION

4. FIRST AID MEASURES

Inhalation

Product Name : OBEEN UF3

Remove the source of contamination or move the victim to fresh air. Ensure airways are clear and have qualified person give oxygen through a facemask if breathing is difficult. If irritation develops and persists, seek medical attention.

Ingestion

DO NOT induce vomiting. Immediately wash out mouth with water. Seek medical attention.

Skin

Remove all contaminated clothing. Wash gently and thoroughly with water and non-abrasive soap. Ensure contaminated clothing is washed before re-use or discard. If irritation develops and persists, seek medical attention.

Eye

If contact with the eye(s) occur, wash with copious amounts of water for approximately 15 minutes holding eyelids(s) open. Take care not to rinse contaminated water into the non-affected eye. If irritation develops and persists, seek medical attention.

First Aid Facilities

Eye wash and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Extinguishing Media

Carbon dioxide, dry chemical, or foam.

Do NOT use water jets. Cool fire exposed containers with water spray.

Specific Methods

Self-Contained Breathing Apparatus (S.C.B.A) and full protective clothing should be worn to minimise exposure.

Specific Hazards

Combustible substance. Fire-exposed container may rupture/explode.

6. ACCIDENTAL RELEASE MEASURES

Other Information

SMALL - 20 LITRES OR LESS

Soak up on Castrol Diatomaceous Earth or similar inert oil absorbent. Arrange for disposal through an approved facility.

LARGE - GREATER THAN 20 LITRES

Remove all sources of ignition. Increase ventilation. Evacuate all unnecessary personnel. Wear full protective equipment and clothing to minimise exposure. If possible contain the spill. Place inert absorbent material such as vermiculite, sand or dirt onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. Do not dilute material

but contain. If large quantities of this material enter the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.

7. HANDLING AND STORAGE

Handling

Repeated or prolonged contact with this material should be avoided in order to lessen the possibility of skin disorders. It is essential that all who come into contact with lubricants and industrial oils maintain high standards of personal hygiene ie. washing hands prior to eating, drinking or going to the toilet. Build-up of mists in the working atmosphere must be prevented. Misuse of empty containers can be hazardous. Do not cut, weld, heat or drill containers. Residue may ignite with explosive violence if heated sufficiently. Do not pressurise or expose to open flame or heat. Keep container closed and bung in place.

Storage

Classified as a combustible substance for storage and handling purposes. Store in a cool, dry, well-ventilated area, out of direct sunlight. Avoid sparks, flames, and other ignition sources. Store away from incompatible materials such as materials that support combustion (oxidising materials). Reference should be made to Australian Standard AS1940- The storage and handling of flammable and combustible liquids.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Exposure Limits

No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC). However, Exposure Standards for oil mist are listed below.

| SUBSTANCE | TWA | | STEL | |
|-------------------|-----|-------------------|------|-------------------|
| | ppm | mg/m ³ | ppm | mg/m ³ |
| Oil mist, mineral | - | 5 | - | 10 |

Respiratory Protection

Avoid breathing of vapours, mists or spray. Where ventilation is inadequate and vapours or mists are generated the use of an approved respirator with organic vapour and dust/mist filter complying with AS/NZS 1715 and AS/NZS 1716 is recommended. Filter capacity and respirator type depends on exposure levels.

Eye Protection

Safety glasses or face shield as appropriate. Refer to the Australian Standard AS/NZS 1337- Eye Protectors for Industrial Applications.

Hand Protection

Impervious gloves such as neoprene or nitrile recommended.

Body Protection

PVC or nitrile apron where clothing is likely to be contaminated.

Eng. Controls

Where vapours or mists are generated and exposure standards are exceeded, the use of respiratory protection, or a local exhaust ventilation system is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Transparent pale yellow grease.

Melting Point

235°C

Boiling Point

Not available

Solubility in Water

Insoluble

Specific Gravity

(H₂O=1)

0.8580 @ 15.5°C

pH Value

Not applicable

Vapour Pressure

Not available

Viscosity

Not available

Flash Point

228°C (Method: ISO2592)

Flammability

Combustible substance. Remove all sources of heat and ignition.

Ignition Temperature

Not available

Flammable Limits LEL

Not available

Flammable Limits UEL

Not available

10. STABILITY AND REACTIVITY

Stability

Stable under normal conditions of storage and handling.

**Hazardous
Polymerization**

Will not occur.

Materials to Avoid

Strong oxidising agents.

**Hazardous
Decomposition
Products**

Oxides of carbon, nitrogen, sulphur and phosphorus.

11. TOXICOLOGICAL INFORMATION

**Toxicology
Information**

No component known to be present in this product at >0.1% is presently listed as a carcinogen by the IARC, NTP or OSHA.

Inhalation

May cause irritation to the mucous membrane and upper airways, especially if the material is heated or mists are generated and/or is used in poorly ventilated areas. Symptoms may include headache, dizziness and nausea.

Ingestion

May cause irritation to the mouth, oesophagus and stomach. Symptoms may include nausea, vomiting and diarrhoea.

Skin

Unlikely to irritate on brief contact. Repeated or prolonged contact may dry and defat the skin, resulting in skin irritation and possible dermatitis.

Eye

May cause slight to moderate transient eye irritation, resulting in redness, stinging and lachrymation.

Chronic Effects

Prolonged or repeated contact with this material may result in skin irritation leading to dermatitis.

12. ECOLOGICAL INFORMATION

Environ. Protection

Prevent this material from entering the environment.

Other Information

No specific ecological data available for this product.

13. DISPOSAL CONSIDERATIONS

Waste Disposal

Dispose of waste according to federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

14. TRANSPORT INFORMATION

Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

U.N. Number

None Allocated

Proper Shipping Name

None Allocated

DG Class

None Allocated

Hazchem Code

None Allocated

Packing Group

None Allocated

15. REGULATORY INFORMATION

Poisons Schedule

Not Scheduled

16. OTHER INFORMATION

Contact Person/Point

For information concerning details on this Safety Data Sheet contact your local Technical Services Manager on the following numbers:-

Sydney: (02) 9795 4800
Melbourne: (03) 9268 4200
Brisbane: (07) 3850 9300
Adelaide: (08) 8347 6200
Perth: (08) 9268 9288

Castrol Technical Help Line 1300 557 998 (Local call)

IMPORTANT DISCLAIMER

All reasonable care has been taken to ensure that the information and advice contained herein are accurate at the time of printing. However, Castrol accepts no tortious or contractual liability for any loss or damages suffered as a consequence of reliance on the information and advice contained herein.

24 HOUR EMERGENCY CONTACT

Product Name : OBEEN UF3

1 800 638 556
24 HOUR EMERGENCY CONTACT (New Zealand Only)
0800 154 666

...End Of MSDS...