

# SAFETY DATA SHEET

FOR INDUSTRIAL USE ONLY

SS4120

## Section 1. Product and company identification

**Product name** : SS4120  
**Chemical name** : Not available

**Manufacturer/Importer** : Momentive Amer Ind.

**Distributor Information** : DC Products Pty Limited  
Unit 117 45 Gilby Road  
Mount Waverley 3149 Australia

**Contact person** : Viren Kumar

**Telephone** : +61 3 95588898

**Emergency telephone number  
Supplier** : 61 418 529 118

## Section 2. Hazards identification

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 2  
ACUTE TOXICITY:oral - Category 3  
ACUTE TOXICITY:dermal - Category 3  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
TOXIC TO REPRODUCTION - Category 1B  
TOXIC TO REPRODUCTION - Category 1B  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)  
- Category 1  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)  
[Narcotic effects] - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED  
EXPOSURE) - Category 1

### GHS label elements

**Hazard pictograms** :



**Signal word** :

Danger

**Hazard statements** :

H225 Highly flammable liquid and vapor.  
H301 Toxic if swallowed.  
H311 Toxic in contact with skin.  
H319 Causes serious eye irritation.  
H360F May damage fertility.  
H360 May damage the unborn child.  
H370 Causes damage to organs:  
H336 May cause drowsiness and dizziness.  
H372 Causes damage to organs through prolonged or repeated

exposure:

### Precautionary statements

<b>General</b>	:	Not applicable.
<b>Prevention</b>	:	<p>Obtain special instructions before use.            Do not handle until all safety precautions have been read and understood.            Use personal protective equipment as required. Wear protective gloves.            Wear eye or face protection. Wear protective clothing.            Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.            Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.            Use only non-sparking tools.            Take precautionary measures against static discharge. Keep container tightly closed.            Use only outdoors or in a well-ventilated area. Do not breathe vapor.            Do not eat, drink or smoke when using this product.            Wash hands thoroughly after handling.</p>
<b>Response</b>	:	<p>Get medical attention if you feel unwell.            IF exposed:            Call a POISON CENTER or physician.  <b>IF INHALED:</b>            Remove victim to fresh air and keep at rest in a position comfortable for breathing.            Call a POISON CENTER or physician if you feel unwell.  <b>IF SWALLOWED:</b>            Immediately call a POISON CENTER or physician.            Rinse mouth.  <b>IF ON SKIN (or hair):</b>            Take off immediately all contaminated clothing.            Rinse skin with water or shower.  <b>IF ON SKIN:</b>            Wash with plenty of soap and water.            Call a POISON CENTER or physician if you feel unwell.  <b>IF IN EYES:</b>            Rinse cautiously with water for several minutes.            Remove contact lenses, if present and easy to do. Continue rinsing.            If eye irritation persists: Get medical attention.</p>
<b>Storage</b>	:	<p>Store locked up.            P403Store in a well-ventilated place.            P235Keep cool.</p>
<b>Disposal</b>	:	P501Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Other hazards which do not result in classification</b>	:	None known.

## Section 3. Composition/information on ingredients

Substance/mixture : Mixture  
 Chemical name : Not available

Hazardous ingredients	% by weight	CAS number
Ethanol	50 - 70	64-17-5
Methanol	30 - 50	67-56-1
Polysilicic acid, ethyl ester	5 - 10	11099-06-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first aid personnel** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing

apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

**Methods and material for containment and cleaning up**

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

**Section 7. Handling and storage****Precautions for safe handling**

- Protective measures** : Put on appropriate personal protective equipment (see section 8 of SDS). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

**Section 8. Exposure controls/personal protection**

**Control parameters**

**Occupational exposure limits**

Ingredient name	Exposure limits
Ethanol	<p><b>OSHA PEL 1989 Vacated (1989-03-01)</b> Time Weighted Average (TWA) 1,900 mg/m<sup>3</sup> 1,000 ppm</p> <p><b>OSHA PEL (1993-06-30)</b> Time Weighted Average (TWA) 1,900 mg/m<sup>3</sup> 1,000 ppm</p> <p><b>NIOSH REL (1994-06-01)</b> Time Weighted Average (TWA) 1,900 mg/m<sup>3</sup> 1,000 ppm</p> <p><b>ACGIH TLV (2008-11-24)</b> Short Term Exposure Limit (STEL) 1,000 ppm</p>
Methanol	<p><b>OSHA PEL 1989 Vacated (1989-03-01)</b> Time Weighted Average (TWA) 260 mg/m<sup>3</sup> 200 ppm</p> <p><b>Pollutant concentration that should not be exceeded during working hours and which workers are believed to be exposed during a period of 15 minutes maximum, without experiencing:</b> a) irritation. b) chronic or irreversible tissue damage. c) dependent toxic effects of exposure rate. d) Narcosis of sufficient magnitude to increase susceptibility to accidents. e) The reduction of ability to get to safety by their own means. 325 mg/m<sup>3</sup> 250 ppm</p> <p><b>OSHA PEL (1993-06-30)</b> Time Weighted Average (TWA) 260 mg/m<sup>3</sup> 200 ppm</p> <p><b>NIOSH REL (1994-06-01)</b> Time Weighted Average (TWA) 260 mg/m<sup>3</sup> 200 ppm</p> <p><b>Pollutant concentration that should not be exceeded during working hours and which workers are believed to be exposed during a period of 15 minutes maximum, without experiencing:</b> a) irritation. b) chronic or irreversible tissue damage. c) dependent toxic effects of exposure rate. d) Narcosis of sufficient magnitude to increase susceptibility to accidents. e) The reduction of ability to get to safety by their own means. 325 mg/m<sup>3</sup> 250 ppm</p> <p><b>ACGIH TLV (1994-09-01)</b> Time Weighted Average (TWA) 262 mg/m<sup>3</sup> 200 ppm</p> <p><b>Short Term Exposure Limit (STEL) 328 mg/m<sup>3</sup> 250 ppm</b></p>

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Individual protection measures**

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product., When there is a risk of ignition from static electricity, wear anti-static protective clothing., For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).  
Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid
- Color** : colorless.
- Odor** : Not available
- Odor threshold** : Not available
- pH** : Not available
- Melting point** : -81.00 °C (113.80- °F) Not applicable.
- Boiling point** : 65 °C (149.00 °F)
- Flash point** : 11 °C (51.80 °F) (calculated.)
- Burning time** : Not available
- Burning rate** : Not available

Evaporation rate	:	Not available
Flammability (solid, gas)	:	Not available
Lower and upper explosive (flammable) limits	:	<b>Lower:</b> Not available <b>Upper:</b> Not available
Vapor pressure	:	Not applicable.
Vapor density	:	Not available
Relative density	:	0.82
Density	:	0.82 g/cm <sup>3</sup>
Solubility	:	SOLUBLE IN ALCOHOLS
Solubility in water	:	Soluble
Partition coefficient: n-octanol/water	:	Not available
Auto-ignition temperature	:	185.00 °C (365.00 °F)
Decomposition temperature	:	Not available
SADT	:	Not available
Viscosity	:	<b>Dynamic:</b> Not available <b>Kinematic:</b> Not available
Volatile organic content	:	100 % (w/w) 794 g/l

**Other information**

No additional information.

## Section 10. Stability and reactivity

Reactivity	:	Stable under normal conditions.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	:	Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

**Information on toxicological effects****Acute toxicity**

Conclusion/Summary : Not determined

**Irritation/Corrosion**



**Conclusion/Summary**

**Skin** : Not determined  
**eyes** : Not determined  
**Respiratory** : Not determined

**Sensitization**

**Conclusion/Summary**

**Skin** : Not determined  
**Respiratory** : Not determined

**Mutagenicity**

**Conclusion/Summary** : Not determined

**Carcinogenicity**

**Conclusion/Summary** : Not determined

**Reproductive toxicity**

**Conclusion/Summary** : Not determined

**Teratogenicity**

**Conclusion/Summary** : Not determined

**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
Ethanol	Category 1 Category 3		central nervous system (CNS) Narcotic effects Respiratory tract irritation
Methanol	Category 3 Category 1 Category 2		Respiratory tract irritation central nervous system (CNS) optic nerve
Polysilicic acid, ethyl ester	Category 3		Respiratory tract irritation

**Specific target organ toxicity (repeated exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
Ethanol	Category 1		liver
Methanol	Category 2		kidneys liver gastrointestinal tract skin respiratory tract

**Aspiration hazard**

Not available

**Information on the likely routes of exposure** : Not available

**Potential acute health effects**

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.
- Skin contact** : Toxic in contact with skin.
- Ingestion** : Toxic if swallowed. Can cause central nervous system (CNS) depression. Irritating to mouth, throat and stomach.

**Symptoms related to the physical, chemical and toxicological characteristics**

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

**Delayed and immediate effects and also chronic effects from short and long term exposure**

**Short term exposure**

- Potential immediate effects** : Not available
- Potential delayed effects** : Not available

**Long term exposure**

- Potential immediate effects** : Not available
- Potential delayed effects** : Not available

**Potential chronic health effects**

- Conclusion/Summary** : Not determined
- General** : Causes damage to organs through prolonged or repeated exposure:
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : May damage the unborn child.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : May damage fertility.

**Numerical measures of toxicity**

**Acute toxicity estimates**

Route	ATE value
-------	-----------

Oral	221.2 mg/kg
<b>Route</b>	<b>ATE value</b>
Dermal	681.8 mg/kg

## Section 12. Ecological information

### Ecotoxicity

**Conclusion/Summary** : Not available

### Persistence/degradability

**Conclusion/Summary** : Not available

### Bioaccumulative potential

Product/ingredient name	Species	Exposure	LogPow	BCF	Potential
Ethanol			-0.35	-	low
Methanol			-0.77	-	low

### Mobility in soil

**Soil/water partition coefficient (KOC)** : Not available

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. See

Section 8 for information on appropriate personal protective equipment.

## Section 14. Transport information

**DOT SHIPPING NAME:** Flammable liquids, n.o.s.(Methanol, ethanol)  
**DOT HAZARD CLASS:** 3  
**DOT LABEL (S):** 3  
**UN/NA NUMBER:** UN1993  
**PACKING GROUP:** II

**IMDG SHIPPING NAME:** Flammable liquids, n.o.s.(Methanol, ethanol)  
**CLASS:** 3  
**IMDG-Labels:** 3  
**UN NUMBER:** UN1993  
**PACKING GROUP:** II  
**EmS No.:** F-E; S-E

**IATA:** Flammable liquids, n.o.s.(Methanol, ethanol)  
**CLASS:** 3  
**ICAO-Labels:** 3  
**UN NUMBER:** UN1993  
**PACKING GROUP:** II

**Special precautions for user** : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.'

## 15.Regulatory information

### United States

**U.S. Federal regulations** : **United States - TSCA 12(b) - Chemical export notification:** None required.  
**United States - TSCA 5(a)2 - Final significant new use rules:** Not listed  
**United States - TSCA 5(a)2 - Proposed significant new use rules:** Not listed  
**United States - TSCA 5(e) - Substances consent order:** Not listed

### SARA 311/312

**Classification** : Fire hazard  
 Immediate (acute) health hazard  
 Delayed (chronic) health hazard

### SARA 313

	Product name	CAS number
<b>Form R - Reporting requirements</b>	: Methanol	67-56-1
<b>Supplier notification</b>	: Methanol	67-56-1

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

**California Prop. 65:** : WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### Canada

**WHMIS (Canada)** : Class B-2: Flammable liquid  
 Class D-1B: Material causing immediate and serious toxic effects (Toxic).  
 Class D-2A: Material causing other toxic effects (Very toxic). Class D-2B: Material causing other toxic effects (Toxic).

### International regulations

**International lists** : **Australia inventory (AICS):** All components are listed or exempted.  
**Canada inventory:** All components are listed or exempted.  
**Japan inventory:** All components are listed or exempted.  
**China inventory (IECSC):** All components are listed or exempted.  
**Korea inventory:** All components are listed or exempted.  
**New Zealand Inventory (NZIoC):** All components are listed or exempted.  
**Philippines inventory (PICCS):** All components are listed or exempted.  
**United States inventory (TSCA 8b):** All components are listed or exempted.  
**Taiwan inventory (CSNN):** All components are listed or exempted.

## Section 16. Other information

### Hazardous Material Information System III (U.S.A.) :

Health	2
Flammability	3
Physical hazards	0

**Caution:** HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

**Full text of abbreviated H statements** : Not applicable.

### History

**Date of printing** : 09/10/2015  
**Date of issue/Date of revision** : 04/29/2015  
**Date of previous issue** : 04/10/2015  
**Version** : 1.3  
**Prepared by** : Product Safety Stewardship  
**Key to abbreviations** : ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 RID = The Regulations concerning the International Carriage of Dangerous Goods

byRail  
UN = United Nations  
**References** : Not available

### **Notice to reader**

Unless otherwise specified in section 1, Momentive Products are intended for industrial application only. They are not intended for specific medical applications, neither for long-lasting (> 30 days) implantation into the human body, injected or directly ingested, nor for the manufacture of multiple usable contraceptives. Keep out of the reach of children.

### **Further Information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

®,\*, and TM indicate trademarks owned by or licensed to Momentive.