

SS4179

# SAFETY DATA SHEET

## 1. Identification

**Product identifier:** SS4179

**Other means of identification**

**Synonyms:** Primer solution

**Recommended use and restriction on use**

**Recommended use:** Primer

**Restrictions on use:** Not known.

**Manufacturer** : Momentive Performance Materials LLC  
260 Hudson River Road  
Waterford NY 12188

**Distributor Information** : DC Products Pty Limited  
Unit 117/45 Gilby Road  
Mount Waverley 3149  
Australia

**Contact person** : viren.kumar@dcproducts.com.au

**Telephone** : +613 9558 8898

**Emergency telephone number** : +61 418 529 118

## 2. Hazard(s) identification

**Hazard Classification**

**Physical Hazards**

Flammable liquids Category 2

**Health Hazards**

Serious Eye Damage/Eye Irritation Category 2A

Skin sensitizer Category 1

Specific Target Organ Toxicity -  
Single Exposure Category 1<sup>1</sup>.

Specific Target Organ Toxicity -  
Single Exposure Category 3<sup>2</sup>.

Specific Target Organ Toxicity -  
Repeated Exposure Category 1<sup>3</sup>.

Specific Target Organ Toxicity -  
Repeated Exposure Category 2<sup>4</sup>.

**Target Organs**

**SS4179**

1. Central nervous system.
2. Narcotic effect.
3. Peripheral nervous system
4. Kidney, Liver, Skin

**Unknown toxicity - Health**

Acute toxicity, oral	0 %
Acute toxicity, dermal	0 %
Acute toxicity, inhalation, vapor	0 %
Acute toxicity, inhalation, dust or mist	0 %

**Label Elements**

**Hazard Symbol:**



**Signal Word:** Danger

**Hazard Statement:** H225; Highly flammable liquid and vapor.  
 H319; Causes serious eye irritation.  
 H317; May cause an allergic skin reaction.  
 H370; Causes damage to organs.  
 H336; May cause drowsiness or dizziness.  
 H372; Causes damage to organs through prolonged or repeated exposure.

**Precautionary Statements**

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/...] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

**Response :** IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Call a poison center/doctor. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use

**SS4179**

alcohol resistant foam for extinction.

**Storage:** Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Other hazards which do not result in GHS classification:** Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

**3. Composition/information on ingredients**

**Mixtures**

Chemical Identity	CAS number	Content in percent (%)*	Notes
ETHYL ACETATE	141-78-6	50 - <100%	# This substance has workplace exposure limit(s).
Methyl Methacrylate	80-62-6	5 - <10%	# This substance has workplace exposure limit(s).
Methanol	67-56-1	3 - <5%	# This substance has workplace exposure limit(s).
DIBENZOYL PEROXIDE	94-36-0	0.1 - <1%	# This substance has workplace exposure limit(s).

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**4. First-aid measures**

**Ingestion:** Do NOT induce vomiting.

**Inhalation:** Move to fresh air.

**Skin Contact:** Wash the skin immediately with soap and water. Wash contaminated clothing before reuse. Get medical attention if irritation persists after washing.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

---

**SS4179**

**Most important symptoms/effects, acute and delayed**

<b>Symptoms:</b>	Itching Redness
<b>Hazards:</b>	This product is not expected to produce adverse effects under normal conditions of use and appropriate personal hygiene.

**Indication of immediate medical attention and special treatment needed**

<b>Treatment:</b>	Treatment is symptomatic and supportive.
-------------------	--

---

**5. Fire-fighting measures**

<b>General Fire Hazards:</b>	Do not use water jet as an extinguisher, as this will spread the fire. Use water spray to keep fire-exposed containers cool.
------------------------------	--

**Suitable (and unsuitable) extinguishing media**

<b>Suitable extinguishing media:</b>	Alcohol resistant foam. Carbon dioxide Dry chemical.
--------------------------------------	--

<b>Unsuitable extinguishing media:</b>	Avoid water in straight hose stream; will scatter and spread fire.
--	--

<b>Specific hazards arising from the chemical:</b>	Vapors are flammable and heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Ground container and transfer equipment to eliminate static electric sparks. In case of fire, gives off (emits): Carbon oxides
--	--

**Special protective equipment and precautions for firefighters**

<b>Special fire fighting procedures:</b>	Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Product may charge electrostatically during pouring or filling. All equipment used when handling the product must be grounded.
--	--

<b>Special protective equipment for fire-fighters:</b>	Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.
--	---

---

**6. Accidental release measures**

<b>Personal precautions, protective equipment and emergency procedures:</b>	Avoid contact with eyes, skin, and clothing. Keep out of reach of children. Attention: Not for injection into humans.
---	---

<b>Methods and material for containment and cleaning up:</b>	Warn other workers of spill. Wear proper protective equipment as specified in the protective equipment section. Wipe, scrape, or soak up in an inert material and put in a container intended for flammable materials for disposal.
--	---

**SS4179**

**Notification Procedures:** ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

**Environmental Precautions:** Avoid discharge into drains, water courses or onto the ground.

**7. Handling and storage**

**Precautions for safe handling:** Sensitivity to static discharge is expected; material has a flash point below 200 F. Do not get in eyes, on skin, on clothing. Do not taste or swallow. Use only in well-ventilated areas. Wash thoroughly after handling. Product may charge electrostatically during pouring or filling. All equipment used when handling the product must be grounded.

**Conditions for safe storage, including any incompatibilities:** No data available.

**8. Exposure controls/personal protection**

**Control Parameters**

**Occupational Exposure Limits**

Chemical Identity	Type	Exposure Limit Values	Source
ETHYL ACETATE	TWA	400 ppm	US. ACGIH Threshold Limit Values (03 2015)
	REL	400 ppm 1,400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	400 ppm 1,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	400 ppm 1,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	400 ppm 1,400 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	3,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	1,440 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	870 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	400 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	400 ppm 1,400 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
Methyl Methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (03 2015)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (03 2015)
	REL	100 ppm 410 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	100 ppm 410 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 410 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)

**SS4179**

	AN ESL		210 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		860 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		210 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		50 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	50 ppm	205 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	STEL	100 ppm	410 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
Methanol	TWA	200 ppm		US. ACGIH Threshold Limit Values (03 2015)
	STEL	250 ppm		US. ACGIH Threshold Limit Values (03 2015)
	STEL	250 ppm	325 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	200 ppm	260 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	200 ppm	260 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	200 ppm	260 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	250 ppm	325 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	200 ppm	260 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	250 ppm	325 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL		2,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		1,600 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		3,900 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		3,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	200 ppm	260 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	Ceiling	1,000 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	STEL	250 ppm	325 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
DIBENZOYL PEROXIDE	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA		5 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
DIBENZOYL PEROXIDE -	ST ESL		50 µg/m3	US. Texas. Effects Screening Levels (Texas

**SS4179**

Particulate.			Commission on Environmental Quality) (11 2016)
	AN ESL	5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
DIBENZOYL PEROXIDE	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)

**Biological Limit Values**

Chemical Identity	Exposure Limit Values	Source
Methanol (methanol: Sampling time: End of shift.)	15 mg/l (Urine)	ACGIH BEI (03 2015)

**Appropriate Engineering Controls**

Provide eyewash station and safety shower. If the formation of aerosol/mist cannot be excluded, ensure effective exhaust ventilation in the working area.

**Individual protection measures, such as personal protective equipment**

- General information:** Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.
- Eye/face protection:** Face shield Monogoggles
- Skin Protection**
  - Hand Protection:** Rubber or plastics gloves
  - Other:** Wear rubber apron. Wear suitable protective clothing and eye/face protection.
- Respiratory Protection:** If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).
- Hygiene measures:** Observe good industrial hygiene practices. Wash hands after handling. When using do not eat, drink or smoke. It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible.

**9. Physical and chemical properties**

**Appearance**

- Physical state:** liquid
- Form:** liquid
- Color:** Colorless

---

**SS4179**

<b>Odor:</b>	ester like
<b>Odor threshold:</b>	No data available.
<b>pH:</b>	No data available.
<b>Melting point/freezing point:</b>	No data available.
<b>Initial boiling point and boiling range :</b>	ca. 80 °C
<b>Flash Point:</b>	-2.80 °C (Tagliabue Closed Cup)
<b>Evaporation rate:</b>	ca. 6
<b>Flammability (solid, gas):</b>	No data available.
<b>Upper/lower limit on flammability or explosive limits</b>	
<b>Flammability limit - upper (%):</b>	11.00 %(V)
<b>Flammability limit - lower (%):</b>	2.00 %(V)
<b>Explosive limit - upper (%):</b>	No data available.
<b>Explosive limit - lower (%):</b>	No data available.
<b>Heat of combustion:</b>	No data available.
<b>Vapor pressure :</b>	Not applicable
<b>Vapor density:</b>	No data available.
<b>Density:</b>	ca. 0.91 g/cm <sup>3</sup>
<b>Relative density:</b>	0.91
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	Insoluble
<b>Solubility (other):</b>	SOLUBLE IN ALCOHOLS
<b>Partition coefficient (n-octanol/water) Log Pow:</b>	No data available.
<b>Auto-ignition temperature :</b>	385.00 °C
<b>Decomposition temperature:</b>	No data available.
<b>SADT:</b>	No data available.
<b>Viscosity, dynamic:</b>	No data available.
<b>Viscosity, kinematic:</b>	No data available.
<b>VOC:</b>	859 g/l ;

---

**10. Stability and reactivity**

<b>Reactivity:</b>	No dangerous reaction if used as recommended.
<b>Chemical Stability:</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions:</b>	Hazardous polymerisation does not occur.
<b>Conditions to avoid:</b>	Keep away from sources of ignition - No smoking.
<b>Incompatible Materials:</b>	Oxidizing agents.



**SS4179**

**Hazardous Decomposition Products:** Methanol Formaldehyde. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

---

**11. Toxicological information**

**Information on likely routes of exposure**

**Ingestion:** No data available.  
**Inhalation:** No data available.  
**Skin Contact:** No data available.  
**Eye contact:** No data available.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Ingestion:** No data available.  
**Inhalation:** No data available.  
**Skin Contact:** No data available.  
**Eye contact:** No data available.

**Information on toxicological effects**

**Acute toxicity (list all possible routes of exposure)**

**Oral**

**Product:** ATEmix: 3,333.33 mg/kg

**Specified substance(s):**

ETHYL ACETATE LD 50 (Rat, No data available.): 5,620 mg/kg  
LD 50 (Guinea Pig, No data available.): 5,500 mg/kg  
LD 50 (Mouse, No data available.): 4,100 mg/kg  
LD 50 (Rabbit, No data available.): 4,935 mg/kg

Methyl Methacrylate LD 50 (Rat): 7,872 mg/kg

DIBENZOYL PEROXIDE LD 50 (Rat): 6,400 mg/kg

**Dermal**

**Product:** ATEmix: 10,000 mg/kg

**Specified substance(s):**

ETHYL ACETATE LD 50 (Rabbit, No data available.): 20,000 mg/kg  
LD 50 (Rabbit, No data available.): 20,000 mg/kg

**Inhalation**

**SS4179**

**Product:** ATEmix: 60.74 mg/l

**Specified substance(s):**  
ETHYL ACETATE LC50 (Rat, No data available.): 1.6 mg/l  
LC50 (Mouse, No data available.): 45 mg/l

**Repeated dose toxicity**

**Product:** No data available.

**Skin Corrosion/Irritation**

**Product:** No data available.

**Serious Eye Damage/Eye Irritation**

**Product:** No data available.

**Respiratory or Skin Sensitization**

**Product:** No data available.

**Carcinogenicity**

**Product:** No data available.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

No carcinogenic components identified

**US. National Toxicology Program (NTP) Report on Carcinogens:**

No carcinogenic components identified

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Germ Cell Mutagenicity**

**In vitro**

**Product:** No data available.

**In vivo**

**Product:** No data available.

**Reproductive toxicity**

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure**

**SS4179**

**Target Organs**

- Specific Target Organ Toxicity - Single Exposure: Central nervous system.
- Specific Target Organ Toxicity - Single Exposure: Narcotic effect.
- Specific Target Organ Toxicity - Repeated Exposure: Peripheral nervous system
- Specific Target Organ Toxicity - Repeated Exposure: Kidney, Liver, Skin

**Aspiration Hazard**

**Product:** No data available.

**Other effects:** No data available.

**12. Ecological information**

**Ecotoxicity:**

**Acute hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

ETHYL ACETATE LC50 (Leuciscus idus, 48 h): ca. 270 mg/l  
 LC50 (Pimephales promelas, 96 h): 230 mg/l

Methanol LC50 (Pimephales promelas, 96 h): 28,100 mg/l

**Aquatic Invertebrates**

**Product:** No data available.

**Specified substance(s):**

ETHYL ACETATE LC0 (Daphnia magna): 1,562 mg/l  
 (Daphnia magna): 3,090 mg/l

**Chronic hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Aquatic Invertebrates**

**Product:** No data available.

**Toxicity to Aquatic Plants**

**Product:** No data available.

**Persistence and Degradability**

**Biodegradation**

---

**SS4179**

**Specified substance(s):**  
ETHYL ACETATE 68 % (5 d, No data available.)  
85 % (28 d, No data available.)

**BOD/COD Ratio**  
**Product:** No data available.

**Bioaccumulative potential**  
**Bioconcentration Factor (BCF)**  
**Product:** No data available.

**Partition Coefficient n-octanol / water (log Kow)**  
**Product:** No data available.

**Mobility in soil:** No data available.

**Known or predicted distribution to environmental compartments**  
ETHYL ACETATE No data available.  
Methyl Methacrylate No data available.  
Methanol No data available.  
DIBENZOYL PEROXIDE No data available.

**Other adverse effects:** No data available.

---

**13. Disposal considerations**

**General information:** The generation of waste should be avoided or minimized wherever possible. Do not discharge into drains, water courses or onto the ground. See Section 8 for information on appropriate personal protective equipment.

**Disposal instructions:** Disposal should be made in accordance with federal, state and local regulations.

**Contaminated Packaging:** Dispose of as unused product.

---

**14. Transport information**

**DOT**

UN Number: UN 1993  
UN Proper Shipping Name: Flammable liquids, n.o.s.(ETHYL ACETATE, METHANOL)  
Transport Hazard Class(es)  
Class: 3  
Label(s): 3  
Packing Group: II  
Marine Pollutant: No

**SS4179**

**IMDG**

UN Number:	UN 1993
UN Proper Shipping Name:	FLAMMABLE LIQUID, N.O.S.(ETHYL ACETATE, METHANOL)
Transport Hazard Class(es)	
Class:	3
Label(s):	3
EmS No.:	F-E, S-E
Packing Group:	II
Marine Pollutant:	No
Limited quantity	1.00L
Excepted quantity	E2

**IATA**

UN Number:	UN 1993
Proper Shipping Name:	Flammable liquid, n.o.s.(ETHYL ACETATE, METHANOL)
Transport Hazard Class(es):	
Class:	3
Label(s):	3
Packing Group:	II
Cargo aircraft only Packing	364
Instructions:	
Passenger and cargo aircraft	364
Packing Instructions:	
Limited quantity:	Y341
Packing Instructions:	
Excepted quantity	E2
Environmental Hazards:	Not regulated.
Marine Pollutant:	No

**15. Regulatory information**

**US Federal Regulations**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**  
 None present or none present in regulated quantities.

**CERCLA Hazardous Substance List (40 CFR 302.4):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
ETHYL ACETATE	5,000 lbs.
Methyl Methacrylate	1,000 lbs.
Methanol	5,000 lbs.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

Flammable (gases, aerosols, liquids, or solids)  
 Serious eye damage or eye irritation  
 Respiratory or Skin Sensitization

**SS4179**

Specific target organ toxicity (single or repeated exposure)  
 Hazards Not Otherwise Classified (HNOC)

**SARA 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

**SARA 304 Emergency Release Notification**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
ETHYL ACETATE	5,000 lbs.
Methyl Methacrylate	1,000 lbs.
Methanol	5,000 lbs.

**SARA 311/312 Hazardous Chemical**

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
ETHYL ACETATE	10000 lbs
Methyl Methacrylate	10000 lbs
Methanol	10000 lbs
DIBENZOYL PEROXIDE	10000 lbs

**SARA 313 (TRI Reporting)**

<u>Chemical Identity</u>	<u>Reporting threshold for other users</u>	<u>Reporting threshold for manufacturing and processing</u>
Methyl Methacrylate		
Methanol		

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Methyl Methacrylate	Reportable quantity: 1,000 lbs.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):**

None present or none present in regulated quantities.

**US State Regulations**

**US. California Proposition 65**



**WARNING**  
 Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**US. New Jersey Worker and Community Right-to-Know Act**

<u>Chemical Identity</u>
ETHYL ACETATE
Methyl Methacrylate
Methanol
gamma-Methacryloxypropyltrimethoxysilane
DIBENZOYL PEROXIDE

**SS4179**

**US. Massachusetts RTK - Substance List**

**Chemical Identity**

ETHYL ACETATE  
 Methyl Methacrylate  
 Methanol

**US. Pennsylvania RTK - Hazardous Substances**

**Chemical Identity**

ETHYL ACETATE  
 Methyl Methacrylate  
 Methanol

**US. Rhode Island RTK**

**Chemical Identity**

ETHYL ACETATE  
 Methyl Methacrylate  
 Methanol

**Inventory Status:**

Australia AICS:	y (positive listing)	Remarks: None.
Canada DSL Inventory List:	y (positive listing)	Remarks: None.
EU EINECS List:	y (positive listing)	Remarks: None.
Japan (ENCS) List:	y (positive listing)	Remarks: None.
China Inventory of Existing Chemical Substances:	y (positive listing)	Remarks: None.
Korea Existing Chemicals Inv. (KECI):	y (positive listing)	Remarks: None.
Canada NDSL Inventory:	n (Negative listing)	Remarks: None.
Philippines PICCS:	y (positive listing)	Remarks: None.
US TSCA Inventory:	y (positive listing)	Remarks: None.
New Zealand Inventory of Chemicals:	y (positive listing)	Remarks: None.
Taiwan. Taiwan inventory (CSNN):	y (positive listing)	Remarks: None.

**16. Other information, including date of preparation or last revision**

**HMIS Hazard ID**

<b>Health</b>	4
<b>Flammability</b>	3
<b>Physical Hazards</b>	1
<b>PERSONAL PROTECTION</b>	

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; \*Chronic health effect

**SS4179**

**Revision Date:** No data available.

**Version #:** 3.0

**Further Information:** No data available.

**Disclaimer:**

**Notice to reader**

Unless otherwise specified in section 1, Momentive products are intended for use in the manufacture and/or formulation of products and are not intended for direct consumer use. These products are not intended for long-lasting (> 30 days) implantation, injection or direct ingestion into the human body, nor for use in the manufacture of multiple use contraceptives. Keep out of the reach of children.

**Further Information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safehandling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

®,\*, and TM indicate trademarks owned by or licensed to Momentive.