

Revision nr.10 Dated 12/12/2017 Printed on 01/02/2018 Page n. 1 / 8

## Safety data sheet

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SGM496 WHITE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Silicone grease.

1.3. Details of the supplier of the safety data sheet

Name ACC Silicones LTD

Full address Amber House Showground Road

District and Country TA6 6AJBridgwater (Somerset)

England

Tel. +44(0)1278411400 Fax +44(0)1278411444

e-mail address of the competent person

responsible for the Safety Data Sheet sean.stoodley@acc-silicones.com

1.4. Emergency telephone number

For urgent inquiries refer to For all enquiries except Sweden: +44(0)1278411400

Sweden: Ring 112 vid inträffade förgiftningstillbud och begär giftinformation -

dygnet runt.

Ring 010-456-6700 i mindre brådskande fall - dygnet runt. Allmänna och

förebyggande frågor om

akuta förgiftningar besvaras vardagar kl 9-17.

## SECTION 2. Hazards identification.

## 2.1. Classification of the substance or mixture.

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

Hazard classification and indication: --

#### 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: -

Signal words:

Hazard statements:

**EUH210** Safety data sheet available on request.

Precautionary statements: --

## 2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients.

#### 3.1. Substances.

Information not relevant.



Revision nr.10 Dated 12/12/2017 Printed on 01/02/2018 Page n. 2 / 8

SECTION 3. Composition/information on ingredients. ..../>

3.2. Mixtures.

Contains:

Identification. Conc. %. AMORPHOUS SILICATE HYDRATE

c. %. Classification 1272/2008 (CLP).

CAS. 7631-86-9 10 - 30

EC. 231-545-4

EU. 231-34

INDEX.

Reg. no. 01-2119379499-16-0134

TRIMETHYL BORATE

CAS. 121-43-7 0 - 0.3

Flam. Liq. 2 H225, Repr. 1A H360Fd, STOT SE 1 H370, Acute Tox. 4 H312, Eye Irrit. 2 H319

EC. 204-468-9 INDEX. 005-005-00-1 Reg. no. 01-2119906953-33

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## **SECTION 4. First aid measures.**

#### 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

Substance with a community workplace exposure limit.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

## **SECTION 5. Firefighting measures.**

## 5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

## 5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### SECTION 6. Accidental release measures.

#### 6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.



Revision nr.10 Dated 12/12/2017 Printed on 01/02/2018 Page n. 3 / 8

SECTION 6. Accidental release measures. ..../>

#### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage.**

### 7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s).

Information not available.

## **SECTION 8. Exposure controls/personal protection.**

#### 8.1. Control parameters.

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
GBR	United Kingdom	EH40/2005 Workplace exposure limits

EU OEL EU Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.

AMORPHOUS SILICATE HYDRATE								
Threshold Limit	Threshold Limit Value.							
Type	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	4				INHAL.		
MAK	DEU	4				INHAL.		
WEL	GBR	6				INHAL.		
WEL	GBR	2.4				RESP.		
OEL	EU	6				INHAL.		
OEL	EU	2.4				RESP.		

OLL	LO	۷.٦					INLOI .		
Health - Deriv	ed no-effect	level - DNI	EL / DMEL						
Effects on consumers. Effects on workers						rkers			
Route of ex	•	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chroni	Chronic systemic
								c local	
Inhalation.						4 mg/m3	VND	4 mg/m3	VND

#### Legend:

 $(C) = CEILING \hspace*{0.2cm} ; \hspace*{0.2cm} INHAL = Inhalable \hspace*{0.2cm} Fraction \hspace*{0.2cm} ; \hspace*{0.2cm} RESP = Respirable \hspace*{0.2cm} Fraction \hspace*{0.2cm} ; \hspace*{0.2cm} THORA = Thoracic \hspace*{0.2cm} Fraction.$ 

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

## 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.



Revision nr.10 Dated 12/12/2017 Printed on 01/02/2018 Page n. 4 / 8

## SECTION 8. Exposure controls/personal protection.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION** 

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## **SECTION 9. Physical and chemical properties.**

### 9.1. Information on basic physical and chemical properties.

Appearance paste Colour white Odour characteristic Odour threshold. Not available. Not available. pH. Melting point / freezing point. Not available. Initial boiling point. Not available. Boiling range. Not available. Flash point. °C. 150 Evaporation Rate Not available. Flammability of solids and gases Not available. Lower inflammability limit. Not available. Upper inflammability limit. Not available Lower explosive limit. Not available. Upper explosive limit. Not available. Not available. Vapour pressure. Not available. Vapour density Relative density. Not available. Solubility immiscible with water

Partition coefficient: n-octanol/water Not available.

Auto-ignition temperature.

Auto-ignition temperature.

Viscosity

Explosive properties

Oxidising properties

Not available.

Not available.

Not available.

Not available.

Not available.

**9.2. Other information.**Information not available.

## SECTION 10. Stability and reactivity.

#### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

## 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

## 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.





Revision nr.10 Dated 12/12/2017 Printed on 01/02/2018 Page n. 5 / 8

SECTION 10. Stability and reactivity. .../>>

#### 10.5. Incompatible materials.

Information not available.

#### 10.6. Hazardous decomposition products.

Information not available.

## **SECTION 11. Toxicological information.**

#### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

TRIMETHYL BORATE

LD50 (Oral). 6140 mg/kg (Rat) LD50 (Dermal). 1845 mg/kg (Rabbit)

#### AMORPHOUS SILICATE HYDRATE

LD50 (Oral). > 2000 mg/kg Rat LD50 (Dermal). > 2000 mg/kg Rat LC50 (Inhalation). > 2.2 mg/l/1h Rat

## **SECTION 12. Ecological information.**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

### 12.1. Toxicity.

Information not available.

#### 12.2. Persistence and degradability.

AMORPHOUS SILICATE HYDRATE

Solubility in water. mg/l 0,1 - 100

Biodegradability: Information not available.

## 12.3. Bioaccumulative potential.

AMORPHOUS SILICATE HYDRATE

Partition coefficient: n-octanol/water. 0.53

## 12.4. Mobility in soil.

Information not available.

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects.

Information not available.

## **SECTION 13. Disposal considerations.**

## 13.1. Waste treatment methods.

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

ΕN



# ACC Silicones LTD SGM496 WHITE

Revision nr.10 Dated 12/12/2017 Printed on 01/02/2018 Page n. 6 / 8

SECTION 14. Trans	port information.
-------------------	-------------------

1	4.	1.	UI	N	numbe	er.
---	----	----	----	---	-------	-----

Not applicable.

14.2. UN proper shipping name.

Not applicable.

14.3. Transport hazard class(es).

Not applicable.

14.4. Packing group.

Not applicable.

14.5. Environmental hazards.

Not applicable.

14.6. Special precautions for user.

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

## **SECTION 15. Regulatory information.**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

None

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisarion (Annex XIV REACH).

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Information not available.

German regulation on the classification of substances hazardous to water (VwVwS 2005).

WGK 1: Low hazard to waters

## 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.



Revision nr.10 Dated 12/12/2017 Printed on 01/02/2018 Page n. 7 / 8

## **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2 Repr. 1A Reproductive toxicity, category 1A

STOT SE 1 Specific target organ toxicity - single exposure, category 1

Acute Tox. 4 Acute toxicity, category 4
Eye Irrit. 2 Eye irritation, category 2

H225 Highly flammable liquid and vapour.

**H360Fd** May damage fertility. May damage the unborn child.

H370 Causes damage to organs.
H312 Harmful in contact with skin.
H319 Causes serious eye irritation.

**EUH210** Safety data sheet available on request.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)

ΕN



# ACC Silicones LTD SGM496 WHITE

Revision nr.10 Dated 12/12/2017 Printed on 01/02/2018 Page n. 8 / 8

## SECTION 16. Other information. .../>>

- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified: 02 / 03 / 08 / 11 / 12 / 15 / 16.