

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **AS1502**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Adhesive sealant.**

1.3. Details of the supplier of the safety data sheet

Name **CHT UK BRIDGWATER LTD**
Full address **Amber House Showground Road**
District and Country **TA6 6A Bridgwater (Somerset)**
England
Tel. **+44(0)1278411400**
Fax **+44(0)1278411444**

e-mail address of the competent person responsible for the Safety Data Sheet **info.uk@cht.com**

1.4. Emergency telephone number

For urgent inquiries refer to **For all enquiries except Sweden and Hungary and Australia: +44(0)1278411400****Sweden: Ring 112 vid inträffade förgiftningstillbud och begär giftinformation - dygnet runt.****Ring 010-456-6700 i mindre brådskande fall - dygnet runt. Allmänna och förebyggande frågor om akuta förgiftningar besvaras vardagar kl 9-17.****Hungary: Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ) 1097 Budapest, Nagyvárad tér 2, 06-80-201-199 (zöld szám, ingyenesen, éjjel-nappal hívható) 06-1-4761120****Australia: DC Products Pty Ltd, Unit 117, 45 Gilby Road, Mount Waverley VIC 3149. Tel +61 3 9558 8898, Emergency contact number 0418529118**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1
Skin irritation, category 2H318
H315Causes serious eye damage.
Causes skin irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



SECTION 2. Hazards identification ... / >>

Signal words: Danger

Hazard statements:

H318 Causes serious eye damage.
H315 Causes skin irritation.

Precautionary statements:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280 Wear protective gloves / eye protection / face protection.
P310 Immediately call a POISON CENTER / doctor / . . .
P264 Wash . . . thoroughly after handling.

Contains: METHYLSILANETRIYL-TRIACETATE
DIACETOXYDI-TERT-BUTOXYSILANE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification **x = Conc. %** **Classification 1272/2008 (CLP)**

DIHYDROXPOLYDIMETHYLSILOXANE

CAS 70131-67-8 75 ≤ x < 79

EC

INDEX

Reg. no. Exempt

AMORPHOUS SILICATE HYDRATE

CAS 7631-86-9 11.5 ≤ x < 13

EC 231-545-4

INDEX

Reg. no. 01-2119379499-16-0134

ALUMINIUM POWDER (STABILIZED)

CAS 7429-90-5 4 ≤ x < 4.5

EC 231-072-3

INDEX 013-002-00-1

METHYLSILANETRIYL-TRIACETATE

CAS 4253-34-3 2.5 ≤ x < 3

EC 224-221-9

INDEX

Reg. no. 21-2119987097-22

DIACETOXYDI-TERT-BUTOXYSILANE

CAS 13170-23-5 1.5 ≤ x < 2

EC 236-112-3

INDEX

Reg. no. 01-2119987098-20

ACETIC ACID

CAS 64-19-7 0 ≤ x < 0.1

EC 200-580-7

INDEX 607-002-00-6

Reg. no. 01-2119475328-30

**Flam. Sol. 1 H228, Water-react. 2 H261,
Classification note according to Annex VI to the CLP Regulation: T**

Acute Tox. 4 H302, Skin Corr. 1B H314, Eye Dam. 1 H318, EUH014

Skin Corr. 1B H314, Eye Dam. 1 H318

**Flam. Liq. 3 H226, Skin Corr. 1A H314, Eye Dam. 1 H318,
Classification note according to Annex VI to the CLP Regulation: B**

SECTION 3. Composition/information on ingredients ... / >>**OCTAMETHYLCYCLOTETRASILOXANE**CAS 556-67-2 $0 \leq x < 0.1$

EC 209-136-7

INDEX

Reg. no. 01-2119529238-36

Flam. Liq. 3 H226, Repr. 2 H361f, Aquatic Chronic 4 H413

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

SECTION 6. Accidental release measures ... / >>

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Bekendtgørelse om ændring af bekendtgørelse om grænseværdier for stoffer og materialer ¹ - BEK nr 655 af 31/05/2018
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FIN	Suomi	HTP-VÄRDEN 2018. Koncentrationer som befunnits skadliga. SOCIAL- OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 10/2018
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
HUN	Magyarország	A pénzügyminiszter 7/2018. (VIII. 29.) PM rendelete a munkahelyek kémiai biztonságáról szóló 25/2000. (IX. 30.) EüM–SZCSM együttes rendelet módosításáról
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
NOR	Norge	Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
SVK	Slovensko	Nariadenie vlády Slovenskej republiky č. 355/2006 Z. z. o ochrane zamestnancov pred rizikami súvisiacimi s expozíciou chemickým faktorom pri práci v znení neskorších predpisov
SWE	Sverige	Hygieniska gränsvärden, AFS 2018:1
EU	OEL EU	Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

SECTION 8. Exposure controls/personal protection ... / >>

TLV-ACGIH ACGIH 2019

AMORPHOUS SILICATE HYDRATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	4				INHAL
MAK	DEU	4				INHAL
WEL	GBR	6				INHAL

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					4 mg/m3	VND	4 mg/m3	VND

ALUMINIUM POWDER (STABILIZED)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	10				
VLEP	FRA	5				
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV	NOR	2				
NDS/NDSch	POL	2.5				INHAL
NDS/NDSch	POL	1.2				RESP
NPEL	SVK	4				INHAL
NPEL	SVK	1.5				RESP
NGV/KGV	SWE	5				Som AI, Totaldamm
NGV/KGV	SWE	2				RESP Som AI
TLV-ACGIH		1	0.9			

METHYLSILANETRIYL-TRIACETATE

Predicted no-effect concentration - PNEC

Normal value in fresh water	1	mg/l
Normal value in marine water	0.1	mg/l
Normal value for fresh water sediment	3.4	mg/kg
Normal value for marine water sediment	0.34	mg/kg
Normal value for water, intermittent release	10	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0.145	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1 mg/kg bw/d				
Inhalation			5.1 mg/m3	6.3 mg/m3			31 mg/kg	25 mg/m3
Skin			VND	7.2 mg/kg/d			VND	14.5 mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

DIACETOXYDI-TERT-BUTOXYSILANE

Predicted no-effect concentration - PNEC

Normal value in fresh water	0.02875	mg/l
Normal value in marine water	0.02875	mg/l
Normal value for fresh water sediment	0.03279	mg/kg/d
Normal value for marine water sediment	0.00327	mg/kg/d
	9	
Normal value of STP microorganisms	13.276	mg/l

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Effects on workers					
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	10.69 mg/kg bw/d				
Inhalation			VND	37.2 mg/m3			VND	150.84 mg/m3
Skin			VND	10.69 mg/kg bw/d			VND	21.39 mg/kg bw/d

ACETIC ACID

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	25	10.2	50	20.4	
AGW	DEU	25	10	50 (C)	20 (C)	
MAK	DEU	25	10	50	20	
TLV	DNK	25	10			E
VLA	ESP	25	10	50	20	
HTP	FIN	13	5	25	10	
VLEP	FRA			25	10	
WEL	GBR	25	10	50	20	
AK	HUN	25		50		
VLEP	ITA	25	10	50	20	
TGG	NLD	25		50		
TLV	NOR	25	10	50	20	
NDS/NDSch	POL	25		50		
VLE	PRT	25	10	50	20	
TLV	ROU	25	10	50	20	
NPEL	SVK	25	10	50	20	
NGV/KGV	SWE	13	5	25	10	
OEL	EU	25	10	50	20	
TLV-ACGIH		25	10	37	15	

OCTAMETHYLCYCLOTETRAILOXANE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
OEL	EU		10			RESP

Predicted no-effect concentration - PNEC

Normal value in marine water	0.044	mg/l
Normal value for fresh water sediment	0.128	mg/kg
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	0.16	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers		Effects on workers					
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	61 mg/m3	305 mg/m3	61 mg/m3	305 mg/m3				

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

SECTION 8. Exposure controls/personal protection ... / >>

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. When choosing personal protective equipment, ask your chemical substance supplier for advice. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties
9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	paste	
Colour	silver grey	
Odour	pungent	
Odour threshold	Not available	
pH	Not available	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Boiling range	Not available	
Flash point	> 150 °C	
Evaporation Rate	Not available	
Flammability of solids and gases	Not available	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	Not available	
Vapour density	Not available	
Relative density	1.08	
Solubility	immiscible with water	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	> 400 °C	
Decomposition temperature	Not available	
Viscosity	paste	
Explosive properties	Not available	
Oxidising properties	Not available	

9.2. Other information

Information not available

SECTION 10. Stability and reactivity**10.1. Reactivity**

Information not available

10.2. Chemical stability

Information not available

10.3. Possibility of hazardous reactions

The product may react violently with water.

ACETIC ACID

Risk of explosion on contact with: chromium (VI) oxide,potassium permanganate,sodium peroxide,perchloric acid,phosphorus chloride,hydrogen peroxide.May react dangerously with: alcohols,bromine pentafluoride,chlorosulphuric acid,dichromate-sulphuric acid,ethane diamine,ethylene glycol,potassium hydroxide,strong bases,sodium hydroxide,strong oxidising agents,nitric acid,ammonium nitrate,potassium tert-butoxide,oleum.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

ACETIC ACID

Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials**ACETIC ACID**

Incompatible with: carbonates,hydroxides,phosphates,oxidising substances,bases.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Oral LD50 (Rat) >5000 mg/kg; Dermal LD50 (Rabbit) >2000 mg/kg.

11.1. Information on toxicological effectsMetabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:	Not classified (no significant component)
LD50 (Oral) of the mixture:	>2000 mg/kg
LD50 (Dermal) of the mixture:	Not classified (no significant component)

SECTION 11. Toxicological information ... / >>

AMORPHOUS SILICATE HYDRATE
LD50 (Oral) > 2000 mg/kg Rat
LD50 (Dermal) > 2000 mg/kg Rat
LC50 (Inhalation) > 2.2 mg/l/1h Rat

ACETIC ACID
LD50 (Oral) 3310 mg/kg Rat
LD50 (Dermal) 1060 mg/kg Rabbit
LC50 (Inhalation) 11.4 mg/l/4h Rat

OCTAMETHYLCYCLOTETRASILOXANE
LC50 (Inhalation) 2975 ppm/4h

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

DIACETOXYDI-TERT-BUTOXYSILANE
LC50 - for Fish 192.34 mg/l/96h
EC50 - for Algae / Aquatic Plants 28.75 mg/l/72h

12.2. Persistence and degradability

DIACETOXYDI-TERT-BUTOXYSILANE
Rapidly degradable 79.5% Method: OECD 301 F, Exposure duration: 28 days

SECTION 12. Ecological information ... / >>

ALUMINIUM POWDER (STABILIZED)	
Solubility in water	0 mg/l
Degradability: information not available	
AMORPHOUS SILICATE HYDRATE	
Solubility in water	0,1 - 100 mg/l
Degradability: information not available	
ACETIC ACID	
Solubility in water	> 10000 mg/l
Rapidly degradable	

12.3. Bioaccumulative potential

AMORPHOUS SILICATE HYDRATE	
Partition coefficient: n-octanol/water	0.53
ACETIC ACID	
Partition coefficient: n-octanol/water	-0.17

12.4. Mobility in soil

ACETIC ACID	
Partition coefficient: soil/water	1.153

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

SECTION 16. Other information ... / >>

- LEGEND:- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
 - CE50: Effective concentration (required to induce a 50% effect)
 - CE NUMBER: Identifier in ESIS (European archive of existing substances)
 - CLP: EC Regulation 1272/2008
 - DNEL: Derived No Effect Level
 - EmS: Emergency Schedule
 - GHS: Globally Harmonized System of classification and labeling of chemicals
 - IATA DGR: International Air Transport Association Dangerous Goods Regulation
 - IC50: Immobilization Concentration 50%
 - IMDG: International Maritime Code for dangerous goods
 - IMO: International Maritime Organization
 - INDEX NUMBER: Identifier in Annex VI of CLP
 - LC50: Lethal Concentration 50%
 - LD50: Lethal dose 50%
 - OEL: Occupational Exposure Level
 - PBT: Persistent bioaccumulative and toxic as REACH Regulation
 - PEC: Predicted environmental Concentration
 - PEL: Predicted exposure level
 - PNEC: Predicted no effect concentration
 - REACH: EC Regulation 1907/2006
 - RID: Regulation concerning the international transport of dangerous goods by train
 - TLV: Threshold Limit Value
 - TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
 - TWA STEL: Short-term exposure limit
 - TWA: Time-weighted average exposure limit
 - VOC: Volatile organic Compounds
 - vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
 - WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.
This document must not be regarded as a guarantee on any specific product property.
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.

SECTION 16. Other information ... / >>

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 11 / 15 / 16.

Changed TLVs in section 8.1 for following countries:

GBR,